



Host config

```

set int state TenGigabitEthernet89/0/0 up
set interface ip table TenGigabitEthernet89/0/0 1
set int ip address TenGigabitEthernet89/0/0 172.16.255.254/16
set int state TenGigabitEthernet89/0/1 up
set interface ip table TenGigabitEthernet89/0/1 2
set int ip address TenGigabitEthernet89/0/1 172.17.255.254/16
create memif socket /memif/1.memif0 master
set interface ip table memif0/0 1
set int ip address memif0/0 172.56.1.1/24
create memif socket /memif/1.memif1 master
set interface ip table memif1/0 2
set int ip address memif1/0 172.57.1.1/24
set int state memif0/0 up
set int state memif1/0 up
ip route add 172.17.0.1/32 table 1 via 172.56.1.2
ip route add 172.16.0.1/32 table 2 via 172.57.1.2

```

Container config

```

create memif socket /memif/1.memif0 slave
set int state memif0/0 up
set int ip address memif0/0 172.56.1.2/24
create memif socket /memif/1.memif1 slave
set int state memif1/0 up
set int ip address memif1/0 172.57.1.2/24
ip route add 172.16.0.1/32 via 172.56.1.1
ip route add 172.17.0.1/32 via 172.57.1.1

```